

Features

- AHD & IP Hybrid Design
- Max. recording resolution: 1920 x 1080p
- H.264 video compression
- 2 internal SATA HDD
- HDMI/VGA video outputs
- Video extraction through network or using USB flash drive
- Video management software with sureSIGHT
- Supporting sureLINK for dynamic IP Internet connection
- iView HD for remote monitoring on mobile phones

Dimensions

-Unit: mm



430

Specifications

F© (€

MODEL			JN6216B
	ANALOG CAMERA		AHD (1080p), AHD (720p), PAL, NTSC
VIDEO INPUT	NO. OF CHANNEL		16
	IP CAMERA		TeleEye MP, MQ Series
	NO. OF CHANNEL		8
VIDEO OUTPUT	MAIN	DIGITAL VIDEO	1 channel, 1920 x 1080
		VGA	1 channel, 1920 x 1080
		BNC	CVBS
RECORDING	MODE		Manual, schedule, motion, event-driven
	HD TYPE		SATA X 2 (Max. 6 per HDD)
	MAX. RECORDING RATE PER CHANNEL		1080p: 12 / 15fps 1080p lite: 25 / 30fps 720p: 25 / 30fps WD1: 25 / 30fps MP, MQ: 25 / 30fps
	PLAYBACK		Play, forward, backward, pause, digital zoom
COMMUNICATION	NETWORK		RJ-45 10/100 base-T ethernet (auto sensing)
	CONCURRENT USER		6
	WEB SERVER		Built-in
	TELEMETRY CONTROL		RS 485
	USB		USB2.0 x 2
AUDIO	INPUT		RCA X 4
	OUTPUT		RCA X 1
	IP CAMERA AUDIO INPUT		8
EVENT HANDLING	EVENT TYPE		Video motion detection, External alarm, Video loss
	ACTION TYPE		Local recording, email notification, telemetry preset
	EXTERNAL ALARM INPUT		4
RELAY SWITCH	NO. OF CHANNEL		1
POWER	VOLTAGE		12V DC
	MAX. RATING		15W (without HDD)
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE		-10°C - 50°C
	RELATIVE HUMIDITY		10% - 90%
MECHANICAL DESIGN	DIMENSION		430mm (W) x 305mm (D) x 65mm (H)
	WEIGHT (kg)		2.32

www.TeleEye.com

TeleEye Group

DISTRIBUTED BY:

Hong Kong Bangladesh China Malaysia Philippines South Africa Sri Lanka Turkey U.K.