





Features

- AHD High definition Camera
- Resolution: 1080p
- Wide Dynamic Range
- Vari-focal f=6-22mm
- Day / Night 0.0 Lux (IR ON)
- 80m IR Range
- 4 Privacy Masks
- IP66 Weather Proof Standard
- OSD menu

Dimensions

Unit: mm



Specifications

| | | |
|-----------------------------------|------------------------|--|
| MODEL | | AF42M |
| PICK UP DEVICE | | 1 / 2.8" SONY CMOS |
| EFFECTIVE PIXELS | | 1920 (H) x 1080 (V) |
| RESOLUTION | AHD | 1080P |
| | COMPOSITE VIDEO | 700TVL |
| LENS | | 6 ~ 22mm |
| MIN. ILLUMINATION | | 0.0 Lux (IR ON) |
| IR CUT FILTER | | Yes |
| IR LED / EFFECTIVE RANGE | | 48 IR LEDs plus 2 groups hi-power LEDs / 80m |
| ELECTRONIC SHUTTER CONTROL | | Auto / Manual |
| BACK LIGHT COMPENSATION | | On / Off Switchable |
| WIDE DYNAMIC RANGE | | Yes |
| S / N RATIO | | More than 50dB (AGC OFF) |
| WHITE BALANCE | | Auto / Manual |
| VIDEO OUTPUT CONNECTOR | | BNC, 1.0Vp-p (75Ω , composite) |
| AUTO GAIN CONTROL | | Yes |
| OSD MENU | | Multi-language |
| PRIVACY MASK | | 4 |
| NOISE REDUCTION | | Auto |
| POWER SOURCE | | 12V DC / 10W (IR ON) |
| OPERATING TEMPERATURE | | -20 °C ~ +55 °C |
| WEATHER PROOF STANDARD | | IP66 |
| NET WEIGHT (G) | | 1218 |
| DIMENSION (MM) | | 241 (L) x 214(W) x 134(H) |